


Surface Mounted Batten Series

FB

MODEL	: FB
DESCRIPTION	: Bare Batten Fitting
RECOMMENDED INSTALLATION AREA	: Staircase, Corridors, Pelmet, General Circulation Area
INGRESS PROTECTION (IP)	: IP20
DIFFUSER OPTION	: N/A
REFLECTOR OPTION	: N/A


MODEL	WATTAGE	Length x W(A) x H(B) [mm]		
FB 120	1 x 18w	610	52	75
FB 220	2 x 18w	610	95	83
FB 140	1 x 36w	1220	52	75
FB 240	2 x 36w	1220	95	83
FB 340	3 x 36w	1220	145	83



FBR

MODEL	: FBR
DESCRIPTION	: Batten Fitting c/w metal reflector
RECOMMENDED INSTALLATION AREA	: Plantroom, Factory Area
INGRESS PROTECTION (IP)	: IP20
DIFFUSER OPTION	: N/A
REFLECTOR OPTION	: Epoxy gloss/matt Powder Coating

MODEL	WATTAGE	Length x W(A) x H(B) [mm]		
FBR 120	1 x 18w	610	145	85
FBR 220	2 x 18w	610	185	85
FBR 140	1 x 36w	1220	145	85
FBR 240	2 x 36w	1220	185	85
FBR 340	3 x 36w	1220	235	85



FBR-AR

MODEL	: FBR-AR
DESCRIPTION	: Batten fitting c/w aluminium reflector
RECOMMENDED INSTALLATION AREA	: Hypermarket, Production Area
INGRESS PROTECTION (IP)	: IP20
DIFFUSER OPTION	: N/A
REFLECTOR OPTION	: High Specular, Matt Finish

MODEL	WATTAGE	Length x W(A) x H(B) [mm]		
FBR-AR 120	1 x 18w	610	145	85
FBR-AR 220	2 x 18w	610	185	85
FBR-AR 140	1 x 36w	1220	145	85
FBR-AR 240	2 x 36w	1220	185	85
FBR-AR 340	3 x 36w	1220	235	85

