


Surface Mounted Batten Series

FAR

MODEL	: FAR
DESCRIPTION	: Batten Fitting c/w angle reflector
RECOMMENDED INSTALLATION AREA	: Plantroom, Wallwash Area
INGRESS PROTECTION (IP)	: IP20
DIFFUSER OPTION	: N/A
REFLECTOR OPTION	: Epoxy gloss/matt Powder Coating , High Specular/Matt aluminium reflector


MODEL	WATTAGE	Length x W(A) x H(B) [mm]		
FAR 120	1 x 18w	610	72	128
FAR 220	2 x 18w	610	126	140
FAR 140	1 x 36w	1220	72	128
FAR 240	2 x 36w	1220	126	140
FAR 340	3 x 36w	1220	126	140



FDK-P

MODEL	: FDK-P
DESCRIPTION	: Batten Fitting c/w prismatic diffuser
RECOMMENDED INSTALLATION AREA	: Washroom, Staircase, Corridors
INGRESS PROTECTION (IP)	: IP20
DIFFUSER OPTION	: Prismatic, Opal, Clear
REFLECTOR OPTION	: -

MODEL	WATTAGE	Length x W(A) x H(B) [mm]		
FDK-P 120	1 x 18w	610	65	95
FDK-P 220	2 x 18w	610	100	110
FDK-P 140	1 x 36w	1220	65	95
FDK-P 240	2 x 36w	1220	100	110



FWG

MODEL	: FWG
DESCRIPTION	: Batten Fitting c/w wire guard
RECOMMENDED INSTALLATION AREA	: Carpark, Public Corridor
INGRESS PROTECTION (IP)	: IP20
DIFFUSER OPTION	: N/A
REFLECTOR OPTION	: N/A

MODEL	WATTAGE	Length x W(A) x H(B) [mm]		
FWG 120	1 x 18w	615	70	92
FWG 220	2 x 18w	615	120	92
FWG 140	1 x 36w	1225	70	92
FWG 240	2 x 36w	1225	120	92

