

FB Series

FAR

MODEL	: FAR
DESCRIPTION	: Channel fitting c/w angle reflector
RECOMMENDED INSTALLATION AREA	: Warehouse, Plantroom, Carpark
INGRESS PROTECTION (IP)	: IP20
DIFFUSER OPTION	: N/A
REFLECTOR OPTION	: Epoxy gloss/matt Powder Coating

MODEL	WATTAGE	Length x W(A) x H(B) [mm]		
FAR 1x14w/24w	1 x 14w or 24w	569	52	87
FAR 2x14w/24w	2 x 14w or 24w	569	118	110
FAR 1x28w/54w	1 x 28w or 54w	1169	52	87
FAR 2x28w/54w	2 x 28w or 54w	1169	118	110
FAR 1x35w/49w	1 x 35w or 49w	1469	52	87
FAR 2x35w/49w	2 x 35w or 49w	1469	118	110
FAR 1x80w	1 x 80w	1469	52	87
FAR 2x80w	2 x 80w	1469	118	110



FDK-P

MODEL	: FDK-P
DESCRIPTION	: Channel fitting c/w prismatic diffuser
RECOMMENDED INSTALLATION AREA	: Staircase, Kitchen, Corridor
INGRESS PROTECTION (IP)	: IP20
DIFFUSER OPTION	: Prismatic, Opal
REFLECTOR OPTION	: N/A

MODEL	WATTAGE	Length x W(A) x H(B) [mm]		
FDK-P 1x14w/24w	1 x 14w or 24w	885	70	65
FDK-P 2x14w/24w	2 x 14w or 24w	885	100	80
FDK-P 1x28w/54w	1 x 28w or 54w	1185	70	65
FDK-P 2x28w/54w	2 x 28w or 54w	1185	100	80
FDK-P 1x35w/49w	1 x 35w or 49w	1485	70	65
FDK-P 2x35w/49w	2 x 35w or 49w	1485	100	80
FDK-P 1x80w	1 x 80w	1485	70	65
FDK-P 2x80w	2 x 80w	1485	100	80



FWG

MODEL	: FWG
DESCRIPTION	: Channel fitting c/w wire guard
RECOMMENDED INSTALLATION AREA	: General Public Area
INGRESS PROTECTION (IP)	: IP20
DIFFUSER OPTION	: N/A
REFLECTOR OPTION	: N/A

MODEL	WATTAGE	Length x W(A) x H(B) [mm]		
FWG 1x14w/24w	1 x 14w or 24w	575	70	85
FWG 2x14w/24w	2 x 14w or 24w	575	120	85
FWG 1x28w/54w	1 x 28w or 54w	1175	70	85
FWG 2x28w/54w	2 x 28w or 54w	1175	120	85
FWG 1x35w/49w	1 x 35w or 49w	1475	70	85
FWG 2x35w/49w	2 x 35w or 49w	1475	120	85
FWG 1x80w	1 x 80w	1475	70	85
FWG 2x80w	2 x 80w	1475	120	85

